

Specification



Model	HL-4265-050	HL-4265-100	HL-5280-200	HL-5280-400
Capacity	20~6500 g	40~15000 g	100~25000 g	200~40000 g
Accuracy(3σ) ¹	±2 g	±4 g	±5 g	±10 g
Max.throughput ¹	80 pcs/min	80 pcs/min	52 pcs/min	52 pcs/min
Resolution	0.5 g	1 g	1 g	2 g
Product	Length	110~500 mm	110~500 mm	110~650 mm
	Width	5~400 mm	5~400 mm	5~500 mm
	Height	5~500 mm	5~500 mm	5~500 mm
Belt speed	16~50 m/min	16~50 m/min	16~50 m/min	16~50 m/min
Belt height	750±50 mm			
Classification	1 or 2			
Display (HMI)	10.1 inch color TFT LCD display , Touch panel			
Preset memory	Maximum 199			
Power supply	AC220V ±10% , single phase , 50/60 Hz , 0.4kw			
Environmental conditions	temperature : 0°C~40°C relative humidity : 10~90% non-condensing			
Protection class	IP30 compliance			
Exterior	Stainless steel SUS304 hair line (excluding some parts)			
Data output	RS-232 、 RS-485 、 Ethernet 、 USB(2.0) port			

1.The speed and accuracy vary according to the products to be weighed and the rejector.

Applicable industry

food
pharmaceutical
biotechnology
cosmetic

For use with

large carton

